WATTS®

Model PWDWHCL1 Single-Stage Lead Filtration System

Exposure to lead can severely harm your family – especially young, developing children. With the Watts Pure Water PWDWHCL1 Singe-Stage Lead Filtration system, your customers can protect themselves and their families from the harmful impacts of lead with superior quality filtration at the cold-water tap.

IAPMO R&T WATER QUALITY PLATINUM SEAL IAPMO RESEARCH AND TESTING

UPC®

PWDWHCL1 tested and certified by IAPMO R&T Lab and IAPMO R&T to meet NSF/ANSI 42 standards for the reduction of Chlorine, Taste and Odor, and Class I Particulates; NSF/ANSI 53 for the reduction of Lead and Cyst; and NSF/ANSI 372 for low lead compliance as verified and substantiated by test data.

Protect What Matters Most with Superior Lead Filtration at the Faucet

- Certified to reduce Lead, Cysts, Chlorine Taste and Odor, and Sediment
- Designed and certified to reduce 99.2% of lead in drinking water
- High-capacity, 7,900-gallon, 0.5 micron carbon fiber filter for less frequent filter changes
- High-flow system – 2 gallons per minute
- Up to 4x the capacity of other competitive filter systems
- Quick and easy installation – connects directly to most standard kitchen and bathroom cold water faucets
- Simple and quick quarter-turn filter change out
- No additional hole to drill for faucet in sink or counter-top

Contact your local Watts representative today to order!

Call 1 (800) 224-1299

Watts.com

Ordering Information

Model PWDWHCL1 Single-Stage Lead Filtration System

MODEL NO.	ORDERING CODE	DESCRIPTION
PWDWHCL1	7100575	Single Stage High-Capacity Lead Reduction Filtration System
PWCFHCCL1	7100576	Single Stage High-Capacity Lead Reduction Replacement Filter

Feed Water Requirements

Please review operating pressures, temperatures and water chemistry limitations to ensure compatibility.

	Maximum	Minimum
Operating Temperature:	100°F (37.8°C)	35° F (1.7°C)
Operating Pressure:	125psi (862 kPa)	10psi (69 kPa)
pH Parameters:	10	5
Flow Rate:	2.0 gpm	

Certified Performance

Tested	Average % Reduction
Lead pH 6.5	>99.7%
Lead pH 8.6	>99.2%
Cyst	99.99%
Chlorine	>94.8%
Class I Particulates	99.2%

Get Started Today

USA: T: (800) 224-1299 • F: (978) 794-1848 • Watts.com/PureWater
Canada: T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca/PureWater
Latin America: T: (52) 81-1001-8600 • F: (52) 81-8000-7091 • Watts.com/PureWater

© 2022 Watts